

33808 79

WaspTime

EMPLOYEE TIME CLOCKS



Big Business Tools. Small Business Attitude.

Complete WaspTime solutions include all of the components you need to track employee time and attendance efficiently and accurately. Choose the WaspTime clock that fits your business application.



BARCODE CLOCK

- ▶ Employees clock in and out by swiping a barcoded badge through the clock
- ▶ Features Ethernet connectivity for fast and easy installation
- ▶ Ideal for high-traffic, industrial environments



RFID CLOCK

- ▶ Employees clock in and out by passing an RFID badge in front of the clock
- ▶ RFID badges make it easy for large numbers of employees to clock in quickly
- ▶ Features Ethernet connectivity for fast and easy installation
- ▶ Ideal for high-traffic, industrial environments



BIOMETRIC CLOCK

- ▶ Employees clock in and out using a fingerprint
- ▶ Biometric technology delivers secure log-in and eliminates buddy punching
- ▶ Ethernet connectivity offers quick and easy implementation
- ▶ Ideal for office and retail environments

33808 79

WaspTime

EMPLOYEE TIME CLOCKS



Big Business Tools. Small Business Attitude.

BARCODE CLOCK SPECIFICATIONS

DISPLAY	4 x 7 Blue light LED
DIMENSIONS	W 7.3" x H 4.3" x D 2"
SYMBOLOGIES READ	Code 39 (numeric)
INSTALLATION	Wall-mount or desktop
SUPPORTED INTERFACE	Ethernet, TCP/IP Protocol Optional PoE interface
POWER SUPPLY	DC 9V, 500 mA
ENVIRONMENT	Operating temperature: 32°F to 131°F Relative humidity: 5% to 95%
PART NUMBERS	WaspTime Standard Barcode Solution: 633808523787 WaspTime Pro Barcode Solution: 633808523817 WaspTime Enterprise Barcode Solution: 633808523855 WaspTime Barcode Clock Only: 633808523916

RFID CLOCK SPECIFICATIONS

DISPLAY	4 x 7 Blue light LED
DIMENSIONS	W 7.3" x H 4.3" x D 2"
RFID CARD TYPE	125 KHz, ASK, 64 bits, Manchester coding
INSTALLATION	Wall-mount or desktop
SUPPORTED INTERFACE	Ethernet, TCP/IP Protocol Optional PoE interface
POWER SUPPLY	DC 9V, 500 mA
ENVIRONMENT	Operating temperature: 32°F to 131°F Relative humidity: 5% to 95%
PART NUMBERS	WaspTime Standard RFID Solution: 633808523794 WaspTime Pro RFID Solution: 633808523824 WaspTime Enterprise RFID Solution: 633808523862 WaspTime RFID Clock Only: 633808523923

BIO CLOCK SPECIFICATIONS

DISPLAY	Blue backlight LCD, 128 x 64 pixels
DIMENSIONS	W 7.5" x H 5.5" x D 1.8"
INSTALLATION	Wall-mount
SUPPORTED INTERFACE	Ethernet, TCP/IP Protocol Optional PoE interface
ENVIRONMENT	Operating temperature: 32°F to 113°F Relative humidity: 20% to 80%
PART NUMBERS	WaspTime Standard Biometric Solution: 633808523800 WaspTime Pro Biometric Solution: 633808523831 WaspTime Enterprise Biometric Solution: 633808523879 WaspTime Biometric Clock Only: 633808523930